## LEVELS

# section 16



#### PLF POST LEVEL

Rigid post level made from durable re-inforced ABS plastic. Designed to plumb pipes, posts, level RSJ's and other applications where vertical or horizontal is required. Attached with four powerful magnetic pads for working with steel posts and fitted with a strong elastic band for fixing to non-magnetic surfaces. Two horizontal and one plumb tubular acrylic vials for convenience with an accuracy of 0.1deg (1.75mm/M). Dimensions level 121 x 78mm. Display packed.

Stock No. 75042



#### **2** LDM-40M **DISTANCE MEASURER (40M)**

Measures distances up to 40M/132ft in metric or imperial. The backlight LED screen displays area, volume and indirect measurements with an accuracy of  $\pm 1.5m$ m. The memory function enables addition, multiplications and subtractions. Uses 2 x AAA batteries (not supplied). Display packed.

Stock	Description	
15102	Distance Measurer	
61833	Batteries (4 x AAA)	

CLASS 2





#### 3 LLK3 SELF-LEVELLING LASER LEVEL KIT (3 PIECE)

Designed for use where a constant level or repeat level measurements are required. Applications include alignment of windows, dado rails, kitchen units, stairs, outdoor levelling etc. Class 2 laser projects a horizontal, vertical or cross beam lines on surfaces. Accuracy 0.5mm per 1M =  $0.029^{\circ}$  within the operating distance of 3-8M. Self-levelling range  $\pm 6^{\circ}$ . Supplied with heavy duty adjustable tripod (max. height 1.18M), rotating laser enhancement glasses and three AAA batteries. Comprehensive instruction manual included. Packed in blow mould carrying case with display sleeve.

Stock No.	Description	
88640	Laser Level Kit	
65643	Tripod	_
65644	Glasses	
61833	Batteries (4 x AAA)	-

### 400mm ROTATING LASER LEVEL KIT

Designed for use where a constant level or repeat level measurements are required. Applications include alignment of windows, dado rails, kitchen units, stairs, outdoor levelling etc. One horizontal and vertical vial. Operating distance of 3-8M with an accuracy of 0.5mm per 1M = 0.029° in standard position. Supplied with heavy duty adjustable tripod (max. height 1.18M), rotating base marked 360° for mounting level, laser enhancement glasses, two brass 90° line generating glass prisms and two AAA batteries. Supplied with manual. Packed in blow mould carrying case with display sleeve.

Stock No.	Description	
69580	Laser Level Kit	
65643	Tripod	
65644	Glasses	
61833	Batteries (4 x AAA)	

